

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Mixture identification:

Trade name: White PU NY Matt topcoat

Trade code: **OPP530G10**

UFI: WX5W-S2MY-300E-PDR5

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Surface coating

Uses advised against: Use only for explicitly recommended uses.

1.3. Details of the supplier of the safety data sheet

Company: Sirca S.p.A.

Viale Roma, 85

35010 Sandono di Massanzago (PD) - ITALY

Tel. +39 0499322311

Email: safety@sirca.it

1.4. Emergency telephone number

National Poisons Information Centre:

Phone +353 (0) 1 809 2566

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) n. 1272/2008 (CLP)**

Flam. Liq. 3 Flammable liquid and vapour.

Skin Irrit. 2 Causes skin irritation.

Eye Irrit. 2 Causes serious eye irritation.

STOT SE 3 May cause respiratory irritation.

STOT RE 2 May cause damage to organs through prolonged or repeated exposure.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements**Regulation (EC) No 1272/2008 (CLP):****Hazard pictograms and Signal Word**

Warning

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash your face, hands and every exposed part thoroughly after handling
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P370+P378	In case of fire: Use CO2, Foam, Chemical powders For extinction.
P403+P235	Store in a well-ventilated place. Keep cool.

Contains

xylene [isomer mixture]

Fatty acids, C18-unsatd., trimers, compds. May produce an allergic reaction.
with oleylamine

maleic anhydride May produce an allergic reaction.

Special provisions according to Annex XVII of REACH and subsequent amendments:

None.

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%

Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Mixture identification: White PU NY Matt topcoat

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb.	Classification	Registration Number
20-25 %	xylene [isomer mixture]	CAS:1330-20-7 EC:215-535-7 Index:601-022-00-9	Flam. Liq. 3, H226; Asp. Tox. 1, H304; Eye Irrit. 2, H319; STOT SE 3, H335; STOT RE 2, H373; Skin Irrit. 2, H315; Acute Tox. 4, H312; Acute Tox. 4, H332 Acute Toxicity Estimate : ATE - Oral : 3523 mg/kg bw ATE - Dermal : 1100 mg/kg bw ATE - Inhalation (Vapours) : 11 mg/l	01-2119488216-32-xxxx
3-5 %	ethylbenzene	CAS:100-41-4 EC:202-849-4 Index:601-023-00-4	Flam. Liq. 2, H225; Acute Tox. 4, H332; STOT RE 2, H373; Asp. Tox. 1, H304 Acute Toxicity Estimate : ATE - Oral : 3500 mg/kg bw ATE - Dermal : 15400 mg/kg bw ATE - Inhalation (Vapours) : 17.8 mg/l	01-2119489370-35-xxx
3-5 %	n-butyl acetate	CAS:123-86-4 EC:204-658-1 Index:607-025-00-1	Flam. Liq. 3, H226; STOT SE 3, H336, EUH066 Acute Toxicity Estimate : ATE - Oral : 10736 mg/kg bw ATE - Dermal : 14000 mg/kg bw ATE - Inhalation (Vapours) : 21 mg/l	01-2119485493-29-xxxx
1-2 %	cyclohexanone	CAS:108-94-1 EC:203-631-1 Index:606-010-00-7	Flam. Liq. 3, H226; Acute Tox. 4, H332	01-2119453616-35-xxxx
0.5-1 %	ethyl acetate	CAS:141-78-6 EC:205-500-4 Index:607-022-00-5	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066 Acute Toxicity Estimate :	01-2119475103-46-xxxx

			ATE - Oral : 4934 mg/kg bw ATE - Dermal : 20000 mg/kg bw ATE - Inhalation (Vapours) : 29.3 mg/l	
0.25-0.5 %	propylidynetrimethanol	CAS:77-99-6 EC:201-074-9	Repr. 2, H361 Acute Toxicity Estimate : ATE - Oral : 14700 mg/kg bw ATE - Dermal : 10000 mg/kg bw ATE - Inhalation (Vapours) : 0.85 mg/l	01-2119486799-10-xxxx
0.25-0.5 %	2-methoxy-1-methylethyl acetate	CAS:108-65-6 EC:203-603-9 Index:607-195-00-7	Flam. Liq. 3, H226; STOT SE 3, H336 Acute Toxicity Estimate : ATE - Oral : 8532 mg/kg bw ATE - Dermal : 5000 mg/kg bw ATE - Inhalation (Vapours) : 23.8 mg/l	01-2119475791-29-xxxx
0.0015-0.05 %	Fatty acids, C18-unsatd., trimers, compds. with oleylamine	CAS:85711-55-3 EC:288-315-1	Eye Dam. 1, H318; STOT RE 2, H373; Skin Sens. 1A, H317 Acute Toxicity Estimate : ATE - Oral : 2000 mg/kg bw	01-2119974148-28-xxxx
0.0015-0.05 %	cumene	CAS:98-82-8 EC:202-704-5 Index:601-024-00-X	Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H335; Aquatic Chronic 2, H411; Carc. 1B, H350	
0.0015-0.05 %	methanol	CAS:67-56-1 EC:200-659-6 Index:603-001-00-X	Flam. Liq. 2, H225; STOT SE 1, H370; Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 Specific Concentration Limits: C ≥ 10%: STOT SE 1 H370 3% ≤ C < 10%: STOT SE 2 H371 Acute Toxicity Estimate: ATE - Oral: 2769mg/kg bw ATE - Dermal: 17000mg/kg bw ATE - Inhalation (Vapours): 128.2mg/l	01-2119433307-44-xxxx
< 0.0015%	maleic anhydride	CAS:108-31-6 EC:203-571-6 Index:607-096-00-9	Acute Tox. 4, H302; STOT RE 1, H372; Eye Dam. 1, H318; Skin Corr. 1B, H314; Resp. Sens. 1, H334; Skin Sens. 1A, H317 Specific Concentration Limits: C ≥ 0,001%: Skin Sens. 1A H317 Acute Toxicity Estimate: ATE - Oral: 1090mg/kg bw ATE - Dermal: 2620mg/kg bw ATE - Inhalation (Vapours): 4.35mg/l	01-2119472428-31-xxxx

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

Do not use eyewash or ointment of any kind (before obtaining an examination or advice from an eye specialist).

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and label hazardous.

In case of Inhalation:

In case of inhalation, consult a doctor immediately and show him packing or label.

Remove casualty to fresh air and keep warm and at rest.

If breathing is irregular or stopped, administer artificial respiration.

4.2. Most important symptoms and effects, both acute and delayed

Respiratory tract irritation

Eye damages

Skin Irritation

Contact a poisons centre

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

In case of fire: Use CO₂, Foam, Chemical powders For extinction.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Cool the containers exposed to the fire with water.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non emergency personnel:

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Collect the spilled product with no-sparking tools.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

For emergency responders:

Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Eliminate all unguarded flames and possible sources of ignition. Do not smoke.

Suitable material for taking up: absorbing material, organic, sand

Collect spilled material with non-sparking equipment.

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Keep away from flame and sparks. Avoid accumulating electrostatic charge.
- Place recipients on the ground whilst decanting, and wear anti-static clothing and shoes.
- Avoid contact with skin and eyes, inhalation of vapours and mists.
- Use localized ventilation system.
- Don't use empty container before they have been cleaned.
- Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
- Work clothes must be changed before entering the dining areas.
- Do not eat or drink while working.
- Do not smoke while working.
- See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

- Always keep in a well ventilated place.
- Store at below 30 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Incompatible materials:

- Avoid contact with combustible materials. The product could catch fire.

Instructions as regards storage premises:

- Cool and adequately ventilated.

7.3. Specific end use(s)

- No further recommendations. Refer to point 1.2

Recommendation(s)

- None in particular

Industrial sector specific solutions:

- None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Community Occupational Exposure Limits (OEL)

	OEL Type	Country	Long Term mg/m3	Long Term ppm	Short Term mg/m3	Short Term ppm	Behaviour	Notes
xylene [isomer mixture] CAS: 1330-20-7	(OEL (IT))						Binding	skin
	National	IRELAND	221,000	50,000	442,000	100,000		
	National	CHINA	50,000		100,000			
	ACGIH			100,000		150,000		A4, BEI - URT and eye irr, CNS impair
	EU		221	50	442	100		Skin
ethylbenzene CAS: 100-41-4	(OEL (IT))	ITALY	221,000	50,000	442,000			
	National	ITALY	100,000	20,000	200,000			A3. IBE
	ACGIH		100,000	20,000	200,000			A3, BEI - URT irr, kidney dam (nephropathy), cochlear impair
	National	IRELAND	442,000	100,000	884,000	200,000		
	National	NEW ZEALAND	88,000	20,000	176,000	40,000		skin;oto
n-butyl acetate CAS: 123-86-4	National	CHINA	100,000		150,000			
	EU		442	100	884	200		Skin
	NIOSH	CHINA	200,000		300,000			
	ACGIH			50,000		150,000		Eye and URT irr
	(OEL (IT))	ITALY	241,000	50,000	723,000	150,000		
	TWA (Italia)			150,000		200,000		
	National	IRELAND	241,000	50,000	723,000	150,000		

cyclohexanone CAS: 108-94-1	EU		241	50	723	150		
	(OEL (IT))		40,800	10,000	81,600	20,000		
	National IRELAND		40,800	10,000	81,600	20,000		skin
	National NEW ZEALAND		100,000	25,000				skin
	National CHINA		50,000					
ethyl acetate CAS: 141-78-6	ACGIH			20,000				
	EU		40,8	10	81,6	20		Skin
	National NEW ZEALAND		200,000	200,000				
	(OEL ITALY (IT))		734,000	200,000	1469,000	400,000		
	ACGIH			400,000				
2-methoxy-1-methylethyl acetate CAS: 108-65-6	National IRELAND		734,000	200,000	1468,000	400,000		
	EU		734	200	1468	400		
	National		275,000	50,000	550,000	100,000		
	(OEL (IT))		275,000	50,000	550,000	100,000	Binding	skin
	EU		275	50	550	100		Skin
cumene CAS: 98-82-8	EU		100	20	250	50		Skin
	ACGIH			50				Eye, skin, and URT irr, CNS impair
	(OEL ITALY (IT))		50,000	10,000	250,000	50,000		skin
	National IRELAND		260,000	200,000				
	National NEW ZEALAND		262,000	200,000	328,000	250,000		
methanol CAS: 67-56-1	National CHINA		25,000		50,000			
	(OEL (IT))		260,000	200,000				skin
	ACGIH			200,000		250,000		Skin, BEI - Headache, eye dam, dizziness, nausea
	EU		260	200				Skin
	ACGIH		0,010					(IFV), DSEN, RSEN, A4 - Resp sens
maleic anhydride CAS: 108-31-6	National IRELAND			0,010				

Predicted No Effect Concentration (PNEC) values

	PNEC Limit	Exposure Route	Exposure Frequency	Remark
xylene [isomer mixture] CAS: 1330-20-7	0,327 mg/l	Fresh Water		
	0,327 mg/l	Fresh Water		
	0,327 mg/l	occasional emission		
	6,58 mg/l	Microorganisms in sewage treatments		
	2,31 mg/kg	Soil (agricultural)		dry
	12,46 mg/kg	Marine water sediments		dry
	12,46 mg/kg	Freshwater sediments		dry
ethylbenzene CAS: 100-41-4	0,1 mg/l	Fresh Water		

n-butyl acetate CAS: 123-86-4	0,01 mg/l	Marine water	
	13,7 mg/l	Freshwater sediments	
	13,7 mg/l	Marine water sediments	
	0,1 mg/l	occasional emission	
	0,18 mg/l	Fresh Water	
ethyl acetate CAS: 141-78-6	0,018 mg/l	Marine water	
	0,981 mg/kg	Freshwater sediments	
	0,098 mg/kg	Marine water sediments	
	0,09 mg/kg	Soil (agricultural)	
	35,6 mg/l	STP	
propylidynetrimethanol CAS: 77-99-6	0,26 mg/l	Fresh Water	
	0,026 mg/l	Marine water	
	1,25 mg/kg	Freshwater sediments	
	0,125 mg/kg	Marine water sediments	
	0,24 mg/kg	Soil (agricultural)	
2-methoxy-1-methylethyl acetate CAS: 108-65-6	200 mg/kg	orally (secondary poisoning)	
	650 mg/l	STP	
	1 mg/l	Fresh Water	
	0,1 mg/l	Marine water	
	10 mg/l	occasional emission	
Fatty acids, C18-unsatd., trimers, compds. with oleylamine CAS: 85711-55-3	100 mg/l	Microorganisms in sewage treatments	
	0,351 mg/kg	Marine water sediments	
	3,505 mg/kg	Freshwater sediments	
	0,241 mg/kg	Soil (agricultural)	
	100 mg/l	STP	
methanol CAS: 67-56-1	0,635 mg/l	Fresh Water	
	0,064 mg/l	Marine water	
	0,329 mg/kg	Marine water sediments	dry
	3,29 mg/kg	Freshwater sediments	dry
	0,29 mg/kg	Soil (agricultural)	dry
maleic anhydride CAS: 108-31-6	100 mg/l	STP	
	0,47 mg/kg	Food chain	
	15,4 mg/l	Marine water	
	154 mg/l	Fresh Water	
	1540 mg/l	Intermittent releases (fresh water)	
	100 mg/l	STP	
	23,5 mg/l	Soil (agricultural)	
	7,7 mg/kg/day	Marine water sediments	
	77 mg/kg/day	Freshwater sediments	
	0,038 mg/l	Fresh Water	
	0,004 mg/l	Marine water	
	0,296 mg/kg	Freshwater sediments	
	0,033 mg/kg	Marine water sediments	

0,042 mg/kg Soil (agricultural)
0,428 mg/l occasional emission
44,6 mg/l STP

Derived No Effect Level (DNEL) values

	Worker Industry	Worker Professional	Consumer	Exposure Route	Exposure Frequency	Remark
xylene [isomer mixture] CAS: 1330-20-7	180 mg/Kg- bw/day			Human Dermal	Long Term, systemic effects	
	77 mg/m3		14,8 mg/m3	Human Inhalation	Long Term, systemic effects	
			108 mg/Kg- bw/day	Human Dermal	Long Term, systemic effects	
			1872 mg/m3	Human Inhalation	Long Term, local effects	
			12,5 mg/Kg- bw/day	Human Oral	Long Term, systemic effects	
ethylbenzene CAS: 100-41-4	289 mg/m3		174 mg/m3	Human Inhalation	Short Term, systemic effects	
	289 mg/m3		174 mg/m3	Human Inhalation	Short Term, local effects	
	180 mg/kg/day			Human Dermal	Long Term, systemic effects	
	293 mg/m3			Human Inhalation	Short Term, local effects	
	77 mg/m3			Human Inhalation	Long Term, systemic effects	
n-butyl acetate CAS: 123-86-4		600 mg/m3		Human Inhalation	Short Term, local effects	
		300 mg/m3		Human Inhalation	Long Term, local effects	
		11 mg/kg		Human Dermal	Long Term, systemic effects	
		11 mg/kg		Human Dermal	Short Term, systemic effects	
			300 mg/kg	Human Inhalation	Short Term, local effects	
			35,7 mg/m3	Human Inhalation	Long Term, local effects	
			6 mg/kg	Human Dermal	Short Term, systemic effects	
			2 mg/kg	Human Oral	Long Term, systemic effects	
			2 mg/kg	Human Oral	Short Term, systemic effects	
ethyl acetate CAS: 141-78-6	1468 mg/m3		734 mg/m3	Human Inhalation	Short Term, systemic effects	
	1468 ppm			Human Inhalation	Short Term (acute)	
	63 mg/Kg- bw/day			Human Dermal	Long Term, systemic effects	
	734 mg/m3			Human Inhalation	Long Term, local effects	
	734 mg/m3			Human Inhalation	Long Term, systemic effects	
			4,5 mg/Kg- bw/day	Human Oral	Long Term, systemic effects	
			734 mg/m3	Human Inhalation	Short Term (acute)	
			734 mg/m3	Human Inhalation	Long Term, systemic effects	
			37 mg/Kg- bw/day	Human Dermal	Long Term, local effects	

propylidynetrime thanol CAS: 77-99-6	138,8 mg/kg	367 mg/m3	Human Inhalation	Short Term, local effects
		367 mg/m3	Human Inhalation	Long Term, systemic effects
			Human Dermal	Short Term, systemic effects
		3037,3 mg/m3	Human Inhalation	Short Term, systemic effects
		0,67 mg/kg	Human Dermal	Long Term, systemic effects
		6,61 mg/m3	Human Inhalation	Long Term, systemic effects
		83,3 mg/kg	Human Dermal	Short Term, systemic effects
		925 mg/kg	Human Inhalation	Short Term, systemic effects
		50 mg/kg	Human Oral	Short Term, systemic effects
		1,68 mg/kg	Human Dermal	Long Term, systemic effects
		5,03 mg/m3	Human Inhalation	Long Term, systemic effects
		1,68 mg/kg	Human Oral	Long Term, systemic effects
		153,5 mg/kg	Human Dermal	Long Term, systemic effects
		275 mg/m3	Human Inhalation	Long Term, systemic effects
		54,8 mg/kg/day	Human Dermal	Long Term, systemic effects
2-methoxy-1- methylethyl acetate CAS: 108-65-6		33 mg/m3	Human Inhalation	Long Term, systemic effects
		1,67 mg/kg/day	Human Oral	Long Term, systemic effects
Fatty acids, C18- unsatd., trimers, compds. with oleylamine CAS: 85711-55-3	0,024 mg/kg		Human Dermal	Long Term, systemic effects
		0,012 mg/kg	Human Dermal	Long Term, systemic effects
		0,012 mg/kg	Human Oral	Long Term, systemic effects
methanol CAS: 67-56-1	260 mg/m3	50 mg/m3	Human Inhalation	Short Term, systemic effects
	260 mg/m3	50 mg/m3	Human Inhalation	Long Term, systemic effects
	260 mg/kg/day	50 mg/m3	Human Inhalation	Short Term, local effects
	260 mg/m3	50 mg/m3	Human Inhalation	Long Term, local effects
	40 mg/kg/day	8 mg/Kg-bw/day	Human Dermal	Short Term, systemic effects
	40 mg/kg/day	8 mg/m3	Human Dermal	Long Term, systemic effects
maleic anhydride CAS: 108-31-6	0,2 mg/m3		Human Inhalation	Short Term, local effects

0,081 mg/m3	Human Inhalation	Long Term, local effects
0,04 mg/cm2	Human Dermal	Short Term, local effects
0,04 mg/cm2	Human Dermal	Long Term, local effects
0,2 mg/m3	Human Inhalation	Short Term, systemic effects
0,081 mg/m3	Human Inhalation	Long Term, systemic effects

8.2. Exposure controls

Hygienic and Technical measures

Handle according to good hygiene and safety standards, observing the usual precautions for handling chemical products.

Use adequate ventilation/extraction in the working environment.

The choice of personal protective equipment is left to the provisions of the chemical risk assessment.

Eye protection:

Use eye protection devices. Example: closed safety visors, goggles with side protection. Do not wear contact lenses.

Protection for skin:

Wear work clothes with long sleeves and safety footwear. It is recommended to wear protective overgarments with antistatic properties.

Protection for hands:

Due to the synergistic effect of the substances contained in the formulation it is not possible to identify a single material capable of resisting their combination. Multilayer protective gloves for mixtures of substances may be suitable. Always refer to the protection degree and permeation rate data provided by the glove manufacturer with regard to the substances listed in point 3 of this sheet.

Example:

Butyl: Provides resistance to acids, alcohols, aldehydes, ketones, carboxylic acids and glycol esters. Thickness >0.35 mm; permeation time >240 min.

Viton: Provides resistance to aliphatic, halogenated and aromatic hydrocarbons, alcohols, carboxylic acids, glycol ethers and esters and mineral acids. Thickness >0.35 mm; permeation time >240 min.

Nitrile: Provides resistance from bases, oils, alcohols, aliphatic hydrocarbon solvents, fats and glycol ethers. Thickness >0.35 mm; permeation time >240 min.

Respiratory protection:

Use respiratory protection where ventilation is insufficient or exposure is prolonged.

Use an adequate respiratory protection device, e.g. A2 or in case of presence of dust/aerosols A2P2 or A2P3 .

Thermal Hazards:

N.A.

Environmental exposure controls:

Take all technical precautions necessary to avoid the spread of the product in the surrounding environment.

Check that emissions into the atmosphere comply with current legislation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State: Liquid

Appearance and colour: Liquid white

Odour: characteristic

Odour threshold: Not available for the mixture.

pH: N.A.

Kinematic viscosity: > 20,5 mm2/sec (40 °C)

Melting point / freezing point: > 1 °C / < 0 °C

Initial boiling point and boiling range: > 55 °C

Flash point: 23°C / 60°C

Upper/lower flammability or explosive limits: 20.00 % v/v (UEL). 1.00 % v/v (LEL). (Refer to Substances)

Vapour density: > 1,2 kg/mc

Vapour pressure: Some contained substances may have vapor pressure >=0.1 kPa. Refer to the percentage of Volatile Organic Compounds in section 15.

Relative density: 1.35 kg/l

Solubility in water: Insoluble

Solubility in oil: Soluble

Partition coefficient (n-octanol/water): N.A. to mixtures.

Auto-ignition temperature: 250 °C

Decomposition temperature: N.A.

Flammability: The product is classified Flam. Liq. 3 H226

Particle characteristics:

Particle size: N.A.

9.2. Other information

Viscosity: 40.00 s (" Din cup # 6)
No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Avoid accumulating electrostatic charge.

Vapours can form explosive mixtures with air.

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

vapours potentially dangerous to health may be released.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological Information of the Preparation

a) acute toxicity	Not classified Based on available data, the classification criteria are not met
b) skin corrosion/irritation	The product is classified: Skin Irrit. 2(H315)
c) serious eye damage/irritation	The product is classified: Eye Irrit. 2(H319)
d) respiratory or skin sensitisation	Not classified Based on available data, the classification criteria are not met
e) germ cell mutagenicity	Not classified Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified Based on available data, the classification criteria are not met
g) reproductive toxicity	Not classified Based on available data, the classification criteria are not met
h) STOT-single exposure	The product is classified: STOT SE 3(H335)
i) STOT-repeated exposure	The product is classified: STOT RE 2(H373)
j) aspiration hazard	Not classified Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

xylene [isomer mixture]	a) acute toxicity	ATE - Oral : 3523 mg/kg bw ATE - Dermal : 1100 mg/kg bw ATE - Inhalation (Vapours) : 11 mg/l LD50 Inhalation Rat = 27 mg/l 4h LD50 Oral Rat = 3523 mg/kg LD50 Skin Rabbit = 12126 mg/kg
ethylbenzene	a) acute toxicity	ATE - Oral : 3500 mg/kg bw ATE - Dermal : 15400 mg/kg bw ATE - Inhalation (Vapours) : 17.8 mg/l LD50 Oral Rat = 3500 mg/kg LD50 Oral Rat = 4710 mg/kg body weight LD50 Skin Rabbit = 15400 mg/kg DZSR_004 Inhalation Rat = 4000 Ppm 4h
	d) respiratory or skin sensitisation	Skin Sensitization Skin Cavia porcellus Negative

n-butyl acetate	a) acute toxicity	ATE - Oral : 10736 mg/kg bw ATE - Dermal : 14000 mg/kg bw ATE - Inhalation (Vapours) : 21 mg/l LC50 Inhalation Rat > 21 mg/l 4h LD50 Oral Rat = 10736 mg/kg LD50 Skin Rabbit > 14000 mg/kg	Method OECD linee guide 402
ethyl acetate	a) acute toxicity	ATE - Oral : 4934 mg/kg bw ATE - Dermal : 20000 mg/kg bw ATE - Inhalation (Vapours) : 29.3 mg/l LD50 Skin Rabbit > 20000 mg/kg LD50 Oral Rat = 4934, mg/kg LC50 Inhalation Rat > 29,3 mg/l 4h LD50 Oral Rabbit = 4934 mg/kg body weight	
	b) skin corrosion/irritation	Skin Irritant Skin Rabbit Negative	
	e) germ cell mutagenicity	Genotoxicity Negative	
	j) aspiration hazard	Respiratory Tract Corrosive Inhalation Positive	
propylidynetrimehtanol	a) acute toxicity	ATE - Oral : 14700 mg/kg bw ATE - Dermal : 10000 mg/kg bw ATE - Inhalation (Vapours) : 0.85 mg/l LD50 Oral Rat 14700 mg/kg LC50 Inhalation Rat > 0,85 mg/l 4h LD50 Skin Rabbit > 10000 mg/kg	
2-methoxy-1-methylethyl acetate	a) acute toxicity	ATE - Oral : 8532 mg/kg bw ATE - Dermal : 5000 mg/kg bw ATE - Inhalation (Vapours) : 23.8 mg/l LD50 Oral Rat = 6190, mg/kg LC50 Skin Rat > 5000 mg/kg LC50 Inhalation Mist Rat > 23,8 mg/l 6h LD50 Skin Rat > 2000, mg/kg	ECHA
	b) skin corrosion/irritation	Skin Irritant Skin Rabbit Negative	
	c) serious eye damage/irritation	Eye Irritant Rabbit Negative	
	d) respiratory or skin sensitisation	Skin Sensitization Skin Cavia porcellus Negative	
Fatty acids, C18-unsatd., trimers, compds. with oleylamine	a) acute toxicity	ATE - Oral : 2000 mg/kg bw LD50 Oral Rat Female > 2000 mg/kg	
	b) skin corrosion/irritation	Skin Irritant No Eye Irritant Rabbit Yes	
methanol	a) acute toxicity	ATE - Oral : 2769 mg/kg bw ATE - Dermal : 17000 mg/kg bw ATE - Inhalation (Vapours) : 128.2 mg/l LD50 Oral Rat = 2769 mg/kg LD50 Skin Rabbit = 17000 mg/kg LC50 Inhalation Rat = 128,2 mg/l 4h	
maleic anhydride	a) acute toxicity	ATE - Oral : 1090 mg/kg bw	

ATE - Dermal : 2620 mg/kg bw
 ATE - Inhalation (Vapours) : 4.35 mg/l
 LD50 Oral Rat = 1090 mg/kg body weight
 LD50 Skin Rabbit = 2620 mg/kg body weight
 LD50 Inhalation Rat = 4,35 mg/l 1h

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration $\geq 0.1\%$

11.2. Information on other hazards

None known

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

Not classified for environmental hazards.

No data available for the product

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
xylene [isomer mixture]	CAS: 1330-20-7 - EINECS: 215-535-7 - INDEX: 601-022-00-9	a) Aquatic acute toxicity : EC50 Daphnia = 1 mg/l 48 a) Aquatic acute toxicity : LC50 Fish = 2,6 mg/l 96 a) Aquatic acute toxicity : LC50 Algae = 2,6 mg/l 73 b) Aquatic chronic toxicity : NOEC Algae = 0,44 mg/l 73
ethylbenzene	CAS: 100-41-4 - EINECS: 202-849-4 - INDEX: 601-023-00-4	a) Aquatic acute toxicity : LC50 Fish = 42,3 mg/l 96 b) Aquatic chronic toxicity : NOEC Daphnia = 0,96 mg/l 48h
n-butyl acetate	CAS: 123-86-4 - EINECS: 204-658-1 - INDEX: 607-025-00-1	a) Aquatic acute toxicity : LC50 Fish = 64 mg/l 48 a) Aquatic acute toxicity : EC50 Daphnia = 73 mg/l 24 a) Aquatic acute toxicity : EC50 Algae = 674 mg/l 72
ethyl acetate	CAS: 141-78-6 - EINECS: 205-500-4 - INDEX: 607-022-00-5	a) Aquatic acute toxicity : LC50 Fish = 220 mg/l 96 a) Aquatic acute toxicity : EC50 Daphnia = 154 mg/l 48 a) Aquatic acute toxicity : EC50 Algae = 3300 mg/l 48 b) Aquatic chronic toxicity : NOEC Algae > 100 mg/l 72
propylidynetrimethanol	CAS: 77-99-6 - EINECS: 201-074-9	a) Aquatic acute toxicity : LC50 Fish > 1000 mg/l 96 a) Aquatic acute toxicity : EC50 Daphnia = 13000 mg/l 24 a) Aquatic acute toxicity : EC50 Algae > 1000 ml/l 72 b) Aquatic chronic toxicity : NOEC Daphnia 1000 ml/l 500
2-methoxy-1-methylethyl acetate	CAS: 108-65-6 - EINECS: 203-603-9 - INDEX: 607-195-00-7	a) Aquatic acute toxicity : LC50 Fish Trota iridea = 134 ml/l 96 - Method OECD linee guide 203 a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 408 mg/l 48 - „Method Direttiva 67/548CEE allegato V,C.2

a) Aquatic acute toxicity : ErC50 Algae > 1000 mg/l 72 - Method OECD TG 209

b) Aquatic chronic toxicity : NOEC Daphnia > 100 mg/l - „Metodo OECD TG 211, 21 d

b) Aquatic chronic toxicity : NOEC Fish Oryzias latipes = 47,5 mg/l 14 - Linee Guida 204 per il Test dell'OECD

b) Aquatic chronic toxicity : NOEC Algae Alghe Cloroficee > 1000 mg/l 96 - Linee Guida 201 per il Test dell'OECD

Fatty acids, C18-unsatd., trimers, compds. with oleylamine
CAS: 85711-55-3 - EINECS: 288-315-1

a) Aquatic acute toxicity : LC50 Fish > 100 mg/l 96

a) Aquatic acute toxicity : EC50 Daphnia = 15,2 mg/l 48

a) Aquatic acute toxicity : ErC50 Algae = 7,43 mg/l 72

a) Aquatic acute toxicity : NOEC Fish 150 mg/l 48

a) Aquatic acute toxicity : EC50 Active mud > 1000 mg/l 3

methanol
CAS: 67-56-1 - EINECS: 200-659-6 - INDEX: 603-001-00-X

a) Aquatic acute toxicity : LC50 Fish lepomis macr. = 13500 mg/l 96h

a) Aquatic acute toxicity : EC50 Daphnia = 18000 mg/l 48h

a) Aquatic acute toxicity : EC50 Algae = 2200 mg/l 72h

maleic anhydride
CAS: 108-31-6 - EINECS: 203-571-6 - INDEX: 607-096-00-9

a) Aquatic acute toxicity : LC50 Fish = 75 mg/l 96

a) Aquatic acute toxicity : LC0 Fish = 115 mg/l 48

a) Aquatic acute toxicity : EC50 Algae = 29 mg/l 72

a) Aquatic acute toxicity : EC50 Daphnia = 84 mg/l 24

a) Aquatic acute toxicity : EC50 Daphnia 42,8 mg/l 48

a) Aquatic acute toxicity : EC0 Eisenia foetica 44,6 mg/l 17

No endocrine disruptor substances present in concentration >= 0.1%

12.2. Persistence and degradability

None known

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%

12.6. Endocrine disrupting properties

None known

12.7. Other adverse effects

N.A.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information

14.1. UN number or ID number

1263

14.2. UN proper shipping name

ADR-Shipping Name: PAINT

IATA-Shipping Name: PAINT

IMDG-Shipping Name: PAINT

14.3. Transport hazard class(es)

ADR-Class: 3

IATA-Class: 3

IMDG-Class: 3

14.4. Packing group

ADR-Packing Group: III

IATA-Packing group: III

IMDG-Packing group: III

14.5. Environmental hazards

Toxic ingredients quantity: 0.00

Very toxic ingredients quantity: 0.00

Marine pollutant: No

Environmental Pollutant: No

14.6. Special precautions for user

Road and Rail (ADR-RID):

ADR-Label: 3

ADR - Hazard identification number: -

ADR-Special Provisions: 163 367 650

ADR-Transport category (Tunnel restriction code): 3 (E)

Air (IATA):

IATA-Passenger Aircraft: 355

IATA-Cargo Aircraft: 366

IATA-Label: 3

IATA-Subsidiary hazards: -

IATA-Erg: 3L

IATA-Special Provisions: A3 A72 A192

Sea (IMDG):

IMDG-Stowage and handling: Category A

IMDG-Segregation: -

IMDG-Subsidiary hazards: -

IMDG-Special Provisions: 163 223 367 955

IMDG-Page: N/A

IMDG-Label: N/A

IMDG-MFAG: N/A

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Regulation (EU) n. 2021/849 (ATP 17 CLP)

Regulation (EU) n. 2022/692 (ATP 18 CLP)
Regulation (EU) n. 2023/707
Regulation (EU) n. 2023/1434 (ATP 19 CLP)
Regulation (EU) n. 2023/1435 (ATP 20 CLP)
Regulation (EU) n. 2024/197 (ATP 21 CLP)
Regulation (EU) n. 2020/878
Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:
Restrictions related to the product: 3, 40
Restrictions related to the substances contained: 75
Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1	Lower-tier threshold (tonnes)	Upper-tier threshold (tonnes)
Product belongs to category: P5c	5000	50000
Regulation (EU) No 649/2012 (PIC regulation)		
No substances listed		
German Water Hazard Class.		
Class 3: extremely hazardous.		
SVHC Substances:		
No SVHC substances present in concentration >= 0.1%		

Dir. 2010/75/EC (VOC directive) ; Dir. 2004/42/EC (VOC directive)

Total solid content: 65 - 68 %
Volatile Organic compounds - VOCs = 33 %
Volatile Organic compounds - VOCs = 450 g/L
Of which reactive monomers: 0 %
Total Volatile Organic Carbon (typical value): 28 %
Of which reactive monomers: 0 %

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Code	Description	
EUH066	Repeated exposure may cause skin dryness or cracking.	
H225	Highly flammable liquid and vapour.	
H226	Flammable liquid and vapour.	
H301	Toxic if swallowed.	
H304	May be fatal if swallowed and enters airways.	
H311	Toxic in contact with skin.	
H312	Harmful in contact with skin.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H319	Causes serious eye irritation.	
H331	Toxic if inhaled.	
H332	Harmful if inhaled.	
H335	May cause respiratory irritation.	
H336	May cause drowsiness or dizziness.	
H350	May cause cancer.	
H361	Suspected of damaging fertility or the unborn child.	
H370	Causes damage to organs.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H411	Toxic to aquatic life with long lasting effects.	
Code	Hazard class and hazard category	Description
2.6/2	Flam. Liq. 2	Flammable liquid, Category 2
2.6/3	Flam. Liq. 3	Flammable liquid, Category 3
3.1/3/Dermal	Acute Tox. 3	Acute toxicity (dermal), Category 3

3.1/3/Inhal	Acute Tox. 3	Acute toxicity (inhalation), Category 3
3.1/3/Oral	Acute Tox. 3	Acute toxicity (oral), Category 3
3.1/4/Dermal	Acute Tox. 4	Acute toxicity (dermal), Category 4
3.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4
3.10/1	Asp. Tox. 1	Aspiration hazard, Category 1
3.2/2	Skin Irrit. 2	Skin irritation, Category 2
3.3/1	Eye Dam. 1	Serious eye damage, Category 1
3.3/2	Eye Irrit. 2	Eye irritation, Category 2
3.4.2/1A	Skin Sens. 1A	Skin Sensitisation, Category 1A
3.6/1B	Carc. 1B	Carcinogenicity, Category 1B
3.7/2	Repr. 2	Reproductive toxicity, Category 2
3.8/1	STOT SE 1	Specific target organ toxicity — single exposure, Category 1
3.8/3	STOT SE 3	Specific target organ toxicity — single exposure, Category 3
3.9/2	STOT RE 2	Specific target organ toxicity — repeated exposure, Category 2
4.1/C2	Aquatic Chronic 2	Chronic (long term) aquatic hazard, category 2

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
--	---------------------------------

Flam. Liq. 3, H226	On basis of test data
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
STOT SE 3, H335	Calculation method
STOT RE 2, H373	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive

EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

GefStoffVO: Ordinance on Hazardous Substances, Germany.
 GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
 IARC: International Agency for Research on Cancer
 IATA: International Air Transport Association.
 IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
 IC50: half maximal inhibitory concentration
 ICAO: International Civil Aviation Organization.
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
 IMDG: International Maritime Code for Dangerous Goods.
 INCI: International Nomenclature of Cosmetic Ingredients.
 IRCCS: Scientific Institute for Research, Hospitalization and Health Care
 KAFH: KAFH
 KSt: Explosion coefficient.
 LC50: Lethal concentration, for 50 percent of test population.
 LD50: Lethal dose, for 50 percent of test population.
 LDLo: Leathal Dose Low
 N.A.: Not Applicable
 N/A: Not Applicable
 N/D: Not defined/ Not available
 NA: Not available
 NIOSH: National Institute for Occupational Safety and Health
 NOAEL: No Observed Adverse Effect Level
 OSHA: Occupational Safety and Health Administration
 PBT: Persistent, Bioaccumulative and Toxic
 PGK: Packaging Instruction
 PNEC: Predicted No Effect Concentration.
 PSG: Passengers
 RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
 STEL: Short Term Exposure limit.
 STOT: Specific Target Organ Toxicity.
 TLV: Threshold Limiting Value.
 TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
 vPvB: Very Persistent, Very Bioaccumulative.
 WGK: German Water Hazard Class.

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

Paragraphs modified from the previous revision:

- SECTION 3: Composition/information on ingredients
- SECTION 16: Other information

Fac-simile label

White PU NY Matt topcoat

Regulation (EC) No 1272/2008 (CLP):

Hazard pictograms and Signal Word



Warning

Hazard statements

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash your face, hands and every exposed part thoroughly after handling
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P370+P378	In case of fire: Use CO2, Foam, Chemical powders For extinction.
P403+P235	Store in a well-ventilated place. Keep cool.

Contains

xylene [isomer mixture]

Fatty acids, C18-unsatd., trimers, compds. May produce an allergic reaction.
with oleylamine

maleic anhydride May produce an allergic reaction.

QUANTITY:

SUPPLIER: